

Europäisches Patentamt

European Patent Office

Office européen des brevets



(11)

EP 1 103 479 A1

(12)

EUROPEAN PATENT APPLICATION

published in accordance with Art. 158(3) EPC

(43) Date of publication:

30.05.2001 Bulletin 2001/22

(51) Int. Cl.⁷: **B65D 51/24**, **A61L 9/03**,

B65D 49/12

(21) Application number: 00903704.5

(86) International application number:

PCT/ES00/00048

(22) Date of filing: 11.02.2000

(87) International publication number:

WO 00/48922 (24.08.2000 Gazette 2000/34)

(84) Designated Contracting States:

AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE

(72) Inventor:

BASAGANAS MILLAN, Jordi,

Argenters 2-4-8

Edi. 3c/p

Cerdanyola Del Valles, 08290 Barcelona (ES)

(30) Priority: 15.02.1999 ES 9900299

(74) Representative:

Carpintero Lopez, Francisco

HERRERO & ASOCIADOS, S.L.

Alcalá, 35


28014 Madrid (ES)

(71) Applicant: DBK Espana, S.A.

08290 Cerdanyola del Valles (ES)

(54) PLUG FOR RECEPTACLES CONTAINING EVAPORABLE LIQUIDS

(57) The plug comprises a body (1) permanently coupled to the neck of a container for an air freshener or insect repellent liquid, with evaporation occurring through a wick (11) axially coupled in a concentric passage of the plug itself. An inner part of the axial passage of the plug in which wick (11) is inserted is provided with slits (7) along the main generatrix line, forming sectors (9) provided with semi pyramidal projections (12), defining means which allow motion in the direction of insertion of wick (11) and prevent its displacement in the outwards direction for removing said wick (11) from the plug, which prevents the container on which the plug is applied from being refilled with a product other than the original.



Description

OBJECT OF THE INVENTION

[0001] The present invention relates to a plug for 5
containers of liquids which are meant to be evaporated
to be used as air fresheners and/or elimination of
insects, or similar applications, which plug is comple-
mented by a wick which passes through it axially, with
part of said wick submerged in the liquid contained in 10
the container and another part emerging on the outside,
through which the product contained in the container
may evaporate.

[0002] The object of the invention is to provide a
plug which prevents refilling the container by having 15
means which allow an axial mounting as the wick is
introduced but prevent its extraction or its reuse. That is,
one of the main characteristics of the plug is that it is
provided with internal elements which allow axial dis-
placement of the wick in one sense and prevent dis- 20
placement in the opposite direction, in order to prevent
extraction of the wick once mounted in the plug, thereby
preventing refilling of the container with a liquid other
than the original, as said plug is of the type which are 25
permanently mounted on the neck of the container, so
that it cannot be separated.

BACKGROUND OF THE INVENTION

[0003] There are a number of devices or means 30
used to evaporate air freshener liquids, whether to pro-
vide a pleasant atmosphere in a room or to fill said room
with a product which attacks insects in order to elimi-
nate them.

[0004] Among these numerous systems employed 35
there is one in which the discharge of the liquid of the
container takes place through wick mounted on a plug
coupled to the neck of the container, is that one end of
the wick is immersed in the liquid contained and the 40
other end emerges out to allow the liquid to evaporate.

[0005] This type of plug may be permanently 40
mounted on the container neck, so that it is practically
impossible to remove it without breaking or deforming it,
thus preventing a subsequent correct coupling of the
plug on the container.

[0006] However, the wick, which is generally 45
mounted on an axial orifice of the plug, may be easily
mounted and removed, allowing the container to be
refilled with a liquid other than the original once this is
exhausted, resulting in a reduced safety as this new 50
refilled liquid, other than the original, may be harmful if
used as intended, such as by being inflammable, toxic,
corroding plastic or electric components, etc..

[0007] Furthermore, if the wick may be separated 55
and coupled at will on the plug a serious problem arises,
namely that children may remove the wick attracted by
the pleasant smell of the liquid contained, not only pos-
sibly placing the wick in their mouths, with the ensuing

risk as these products are often toxic, but even ingesting
the contents as the wick has been removed from the
plug.

[0008] A protection device is known for wicks
through which evaporation of an air freshener takes
place, described in Patent WO 98/00177, in which the
plug is attached to a plastic cap which covers the outer
part of the wick, so that the wick is well protected by said
cap, preventing children from sucking it or ingesting the
liquid in which the wick is soaked, and thus the cap must
be removed by suitable means and by an adult in order
to leave part of the wick exposed to allow evaporation of
the liquid in the container on which the plug is coupled,
which obviously does not eliminate the risk that once 15
the container wick is exposed by removing the cap, a
child may extract the wick and ingest the contained liq-
uid.

DESCRIPTION OF THE INVENTION

[0009] The disclosed plug has been designed to
solve the above described problems by means of a sim-
ple yet considerably effective means, based on provid-
ing means which prevent the wick from being separated
or removed from the plug, thus preventing refilling the
container to which said plug is applied.

[0010] More specifically, the plug of the invention, in
the conventional manner, comprises an annular body
with a neck directed inwards, with the top edge retained,
corresponding to the container neck, with the plug
mounted permanently on said container neck, with the
characteristic that said plug has a concentric neck
which emerges and is prolonged axially inwards, with a
number of slits along the main line, which define sectors
meant to embrace and press on the wick, which prefer- 35
ably consists of a cylindrical body which passes through
said axial passage of the plug, so that the internal part
with sectors which embrace and press on the lateral
surface of the wick is complemented by a further con-
centric neck with a slightly larger diameter, also pro- 40
vided with slits parallel to the main line, which press on
the previous ones when the plug is coupled to the con-
tainer neck.

[0011] In order to prevent the wick from being
extracted, that is, moved so that it is separated from the
plug, the aforementioned sectors defined in the axial
and inner neck which press on the lateral surface of the
wick are provided with triangular, or semi-pyramidal,
projections, with their vertex located in an internal or lat-
eral surface of each sector, so that the lateral surfaces
of said projections diverge inwards, defining ramps
which allow the displacement of the wick in one direc-
tion but prevent motion in the opposite direction, that is,
they prevent removing the wick once it is inserted in the
plug except by a strong effort applied on said wick, 45
which would cause it to break and made useless, so
that the plug would be also ruined as it requires a corre-
sponding wick to allow the contained liquid to evaporate.

Thereby the main characteristic is achieved, that the plug is made unrefillable, with the ensuing advantages, such as preventing the container from being filled with a liquid other than the original and preventing children from removing the wick and ingesting the contents.

DESCRIPTION OF THE DRAWINGS

[0012] The described construction and advantages of the ramp of the invention, in accordance with an example of a preferred embodiment, may be further understood in view of the following description made with reference to the accompanying drawings where for purpose of illustration only and in no way meant as a definition of the limits of the invention the following is shown:

Figure 1 shows a side elevation view of a plug for containers of evaporable liquids, according to the object of the present invention.

Figure 2 is a bottom plan view of the plug of the previous figure.

Figure 3 is a top plan view of the plug of figure 1, clearly showing as in figure 2 the internal triangular outline projections provided in the sectors which embrace and press on the wick, through which evaporates the liquid of the container bearing the plug itself.

Figure 4 is a sectional view along the line A-A of figure 2 with the wick coupled axially to the concentric passage defined in the plug itself.

Figure 5 shows a further sectional view in this case along the B-B line of figure 3, also including the wick which as can also be seen in the previous figure is free to move in the direction indicated by the arrow, but which may not move in the opposite direction, preventing said wick from being removed or separated from the plug.

PREFERRED EMBODIMENT OF THE INVENTION

[0013] As may be seen in the figures the plug of the invention applicable to containers of liquids meant to be evaporated for air freshening or removal of insects, where the product has the corresponding properties, includes an annular body (1) in which is defined an internal annular neck (2) with a projection (3) directed inwards and projections (4), which determine means of coupling and retention to the corresponding neck of the container on which the plug is applied, with the characteristic that body (1) is provided with a concentric neck (5) which emerges slightly out and above the body of plug (1), while downwards, that is in the opposite direction, it is prolonged in an internal neck (6) provided with

slits (7) along the main line, so that these slits of the internal and axial neck (6) are also made in wall (8), which is shorter than the length of internal neck (6), although greater in diameter, with wall or annular partition (8) and the wall of neck (6) being concentric and both provided with slits (7) along the main generatrix lines, in each case defining a sector, respectively (9) and (10).

[0014] Based on this construction the corresponding wick (11) which consists of a cylindrical body, is passed through the aforementioned axial concentric neck of the plug in the direction indicated by the arrows of figures 4 and 5, that is, towards the inside of the container bearing the plug.

[0015] Thus, in order to prevent wick (11) from being removed, or rather to prevent it from being moved in the opposite direction, sectors (9) of concentric neck (6) which determines the axial passage, which press on wick (11), are provided with semi-pyramidal projections (12), with a triangular outline, as clearly shown in the figures, so that at the innermost area of the surface of sector (9) the projections begins with an initial zero height to then define its semi pyramidal shape, that is, increasing in width and forming a ramp which, as mentioned above, allows an inwards displacement of wick (11), and so that if said wick is extracted, moving it in the opposite direction, semi-pyramidal projections (12) will stop it, by inserting themselves in the lateral surface of wick (11) so that it cannot be removed except by breaking it, by applying a strong tension to it.

Claims

1. Plug for containers of evaporable liquids, of the type comprising an annular body (1) with a neck (2) for coupling and permanent attachment to the corresponding neck of the container to which it is applied, and provided with an axial concentric passage for placing a cylindrical wick (11), which is partially submerged in the liquid of the container and partially emerges outwards to allow evaporation through it of the liquid of the container, characterised in that the innermost or lowermost passage area of wick (11) comprises a concentric neck (6) provided with slits (7) along the main generatrix line, defining sectors (9) which press on the lateral surface of wick (11), with neck (6) enveloped by another neck of greater diameter (9) which is also provided with slits (7) along the main generatrix line, so that neck (9) is shorter than neck (6); with the property that sectors (9) of said neck (6) which press on wick (11) are provided with triangular semi-pyramidal projections (12) which provide means to allow an inwards displacement of wick (11) and prevent its displacement in the opposite direction, in order to prevent it from being separated from the plug once mounted on it, and preventing refilling of the container on which said plug is

applied.

5

10

15

20

25

30

35

40

45

50

55






FIG. 4
A-A





FIG. 5
B-B

INTERNATIONAL SEARCH REPORT

International application No.
PCT/ES 00/00048

A. CLASSIFICATION OF SUBJECT MATTER IPC 7 : B65D 51/24, A61L 9/03, B65D 49/12 According to International Patent Classification (IPC) or to both national classification and IPC		
B. FIELDS SEARCHED Minimum documentation searched (classification system followed by classification symbols) IPC 7 : A61L, A01M, B65D Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched Electronic data base consulted during the international search (name of data base and, where practical, search terms used)		
C. DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	GB266054 A (GLOBOL), 20 October 1993 (20.10.93), Pages 4-8, Figures 1-8	1
A	ES 2050332 T3 (GLOBOL), 16 May 1994 (16.05.94), Column 4, line 42 – Column 6, Line 42 Figures 1-8	1
A	EP 0740941 A1 (FALP), 6 November 1996 (06.11.96) Column 2, Line 12 – Column 3, line 34 ; Figure	1
A	FR 2724632 A1 (KERPLAS), 22 March 1996 (22.03.96) Page 2, line 33 – page 5, line 28 ; Figures 1-5	1
A	US 5669767 A (BUREAU et al.), 23 September 1997 (23.09.97) Column 2, lines 11-62; Figures 1-3	1
<input type="checkbox"/> Further documents are listed in the continuation of box C. <input checked="" type="checkbox"/> Patent family members are listed in annex.		
* Special categories of cited documents: "A" document defining the general state of the art which is not considered to be of particular relevance "E" earlier document but published on or after the international filing date "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) "O" document referring to an oral disclosure, use, exhibition or other means "P" document published prior to the international filing date but later than the priority date claimed "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art "&" document member of the same patent family		
Date of the actual completion of the international search 11 April 2000 (11.04.00)		Date of mailing of the international search report 19 April 2000 (19.04.00)
Name and mailing address of the ISA/ S.P.T.O.		Authorized officer Telephone No.

INTERNATIONAL SEARCH REPORT
 Information on patent family members

 International Application No
PCT/ ES 00/00048

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
GB 2266054 A	20.10.1993	DE 9205243 U	20.08.1992
ES 2050332 T3	16.05.1994	CA 2058973 A	12.10.1991
		EP 0451331 A	16.10.1991
		DE 4011629 A	17.10.1991
		WO 9115249 A	17.10.1991
		AU 7473991 A	30.10.1991
		AT 101012 T	15.02.1994
		DE 59004523 D	17.03.1994
EP 0740941 A1	06.11.1996	IT B0950073 U	04.11.1996
FR 2724632 A1	22.03.1996	NONE	
US 5669767 A	23.09.1997	CA 2181383 A	19.01.1997
		WO 9704272 A	06.02.1997
		AU 5669767 A	23.09.1997